

constant voltage & triac dimmable

new

ML-PSD10



Picture is indicative only

Technical Information

Power (max): 10W
Max. load wattage: 10W*
Dimmable: Yes (see website)
Input Voltage: 180-250V AC
Output Voltage: 12V DC
IP rating: IP20
Warranty: 2 years
Size: Length 145 mm
Width 55 mm | Height 20 mm

ML-PSD20



Technical Information

Power (max): 20W
Max. load wattage: 20W*
Dimmable: Yes (see website)
Input Voltage: 170-250V AC
Output Voltage: 12V DC
IP rating: IP20
Warranty: 2 years
Size: Length 110 mm
Width 45 mm | Height 26 mm

ML-PSD30



Technical Information

Power (max): 30W
Max. load wattage: 30W*
Dimmable: Yes (see website)
Input Voltage: 170-250V AC
Output Voltage: 12V DC
IP rating: IP20
Warranty: 2 years
Size: Length 150 mm
Width 55 mm | Height 33 mm

ML-PSD80



Technical Information

Power (max): 80W
Max. load wattage: 80W*
Dimmable: Yes (see website for dimming instructions)
Input Voltage: 170-250V AC
Output Voltage: 12V DC
IP rating: IP20
Warranty: 2 years
Size: Length 210 mm
Width 70 mm | Height 42 mm

new

ML-PSD200



Technical Information

Power (max): 200W
Max. load wattage: 200W*
Dimmable: Yes (see website for dimming instructions)
Input Voltage: 170-250V AC
Output Voltage: 12V DC
IP rating: IP66
Warranty: 2 years
Size: Length 256 mm
Width 80 mm | Height 53 mm