

CLEVERTRONICS EL LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Catalogue Number	ELIFE-X-LI-SM-WP
MIC	AUD03520010001
Description	Economy Lithium Lifelight, Weatherproof, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby) 1.3W (Max)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D50 C ₉₀ =D50

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560160	BATT:EcoLith 3.2V 3.0Ah 170mm lead,NoBKT
8050174	Lifelight Head: CT10694-D1
8002986	PCA: ELIFE-X-SMS-LI CT10614-L2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order