

Product data sheet

Characteristics

DCDALCIP250-2

DALI DUAL POWER SUPPLY & INT.



Main

Range	DALI Control
Product brand	Clipsal
Product or component type	Dual power supply and serial interface
Device application	Communication Power supply




Complementary

Output current	≤ 235 mA
[Us] rated supply voltage	110 V AC 50 Hz 240 V AC 60 Hz
Output current	≤ 235 mA line
Supply circuit type	AC
Number of lines feed	2
Number of modules	4
Local signalling	LED
Mounting support	DIN rail

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	208 g
Package 1 Height	7.6 cm
Package 1 width	7.8 cm
Package 1 Length	9.6 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.